

LI400 Extreme Multi-Purpose Grease

Part Number (s): 41-1-158400-1 & 41-1-158400-2

Available Sizes:

400LB Drum

400g Lube-Shuttle® Cartridge



Product Description:

The LI400 series greases are lithium complex thickened greases that represent the most advanced lubricating technology. They are formulated for conditions of extreme pressure and high temperatures but are also ideal for general purpose applications. To increase the adhesiveness and film strength of the LI400 series, they are manufactured with state-of-the-art polymers. They also incorporate specially selected mineral oils, extreme pressure, anti-wear, rust and corrosion additives that give them the performance properties to properly lubricate today's modern equipment.

Specific Applications:

Heavy industrial applications are subject to high heat, loads, shear, and water conditions. Ideal for applications where shock loading is present, and the grease must resist "Squeeze Out". Mining / Construction applications of hitch pins, shackle pins, bushings, kingpins on buckets, excavators, shovels, and loaders. Slack Adjuster for over the road trucks.

Properties:

- Multi-Purpose High-Performance Grease
- Excellent Water Resistance
- Extremely Shear Stable
- Polymer Fortified For Maximum Film Strength
- Tacky, will not "squeeze out"
- Rated for Extreme Pressure
- Excellent Corrosion Protection Rating and Anti-Wear Properties

Type	Value	Value	Unit	Standard
Product Name				
NLGI Grade	1	2		
Thickener	Lithium Complex	Lithium Complex		
Base Oil	Mineral	Mineral		
Texture	Tacky	Tacky		
Color/Appearance	Off-White	Off-White		
Penetration, Worked	323	275	0.1 mm	ASTM D 217
Worked Stability 10k	+9	+10	% Change	ASTM D 217
Dropping Point	500+	500+	F	ASTM D 2265
Oxidation, 100hrs	7	7	psi Drop	ASTM D 942
Water Washout @175F	5	3	%	ASTM D 1264
Rust Test Rating	Pass	Pass	Pass/Fail	ASTM D 1743
Roll Stability	+9	+10	%	ASTM D 1831
4-Ball Wear	0.38	0.38	mm	ASTM D 2266
4-Ball Weld	400	400	kgf	ASTM D 2596
4-Ball LWI	45	45	kgf	ASTM D 2596
Timken OK Load	60	60	lbs	ASTM D 2509
Base Oil Characteristics				
Viscosity @ 100°C	15.2	15.2	cST	ASTM D 445
Viscosity @ 40°C	196	196	cST	ASTM D 445
Viscosity Index	64	71		ASTM D 2270
Flash Point	436	436	°F	ASTM D 92
Pour Point	-10	-10	°F	ASTM D 97

The information contained in this brochure is based on the experience and know-how of AET SYSTEMS, INC. in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this Product Information sheet represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend you consult an AET SYSTEMS, INC. Application Engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our Product Information sheets at any time and without warning. With the publication of this Product Information sheet, all previous editions cease to be valid.

ANY FORM OF REPRODUCTIONS REQUIRES EXPRESS PRIOR WRITTEN PERMISSION FROM AET SYSTEMS, INC.